


BSRC-SUS

前端球螺栓(陶瓷球型)



SUS

耐热温度 200℃



★One Point
前端球材质为陶瓷

本体	球
SUS303	Si ₃ N ₄ (氮化硅陶瓷)

型号	球径	M	L	W	质量 (g)
BSRC 5×8-SUS	Sφ3	M 5×0.8	8	2.5	0.8
BSRC 5×12-SUS			12		1.3
BSRC 5×20-SUS			20		2.3
BSRC 6×10-SUS	Sφ4	M 6×1	10.8	3	1.5
BSRC 6×16-SUS			16.8		2.4
BSRC 6×20-SUS			20.8		3
BSRC 6×25-SUS			25.8		3.9
BSRC 8×10-SUS	Sφ5.5	M 8×1.25	11.2	4	2.6
BSRC 8×12-SUS			13.2		3.2
BSRC 8×20-SUS			21.2		5.7
BSRC 8×25-SUS			26.2		7.3
BSRC 8×30-SUS			31.2		8.9
BSRC10×12-SUS	Sφ7	M10×1.5	13.7	5	5
BSRC10×16-SUS			17.7		6.8
BSRC10×20-SUS			21.7		8.7
BSRC10×25-SUS			26.7		11.2
BSRC10×35-SUS			36.7		16.2
BSRC12×16-SUS	Sφ8.5	M12×1.75	18	6	10
BSRC12×20-SUS			22		12.4
BSRC12×30-SUS			32		19.6
BSRC12×40-SUS			42		28.5

特点

陶瓷材质的球体具有高绝缘性、高硬度所以拥有优秀的耐磨损性。

技术数据

耐热温度 200℃