

GRL-L


单列轴承式导轮(L型)



GRL-S-L
(钢铁制)



GRL-J-L
(树脂制)



★One Point
中载荷规格

类型	本体	轴承、扣环
GRL-S-L	S45C 无电解镀镍	钢铁
GRL-J-L	聚缩醛 黑色	

规格	Do	D	L ₁	L	d	d ₁	d ₂	A	B	轴承型号	适用导轮销			
GRL-S-L	30	30	22	8.5	12	6	17	13	3	606ZZ	-	RLP0606	RLP06E	RLP06S
	40	40	30	11.5	16	8	22	18	4.5	608ZZ	RLP0807F	RLP0807	RLP08E	RLP08S
GRL-J-L	50	50	36	14.5	19	10	26	22	5.5	6000ZZ	RLP1008F	RLP1008	RLP10E	RLP10S
	60	60	42	18	23	12	32	26	6.5	6201ZZ	RLP1210F	RLP1210	RLP12E	RLP12S
	70	70	46	22.5	28	15	35	29	8.5	6202ZZ	-	RLP1511	RLP15E	RLP15S

钢铁制		树脂制	
型号	质量(g)	型号	质量(g)
GRL30S-L	30	GRL30J-L	12
GRL40S-L	75	GRL40J-L	25
GRL50S-L	130	GRL50J-L	40
GRL60S-L	210	-	-
GRL70S-L	300	-	-

特点

- 适用于各种滑动门或搬运线。
- 中载荷规格。
- 轨道可使用市面销售的研磨钢。

相关产品

- RLP-F** 导轮销(凸缘型)
- RLP** 导轮销
- RLP-S** 导轮销(同心型)
- RLP-E** 导轮销(偏心型)

技术数据

轴承的额定载荷

轴承型号	基本动作额定 载荷Cr(N)	基本静止额定 载荷Cor(N)
606ZZ	2,260	840
608ZZ	3,300	1,360
6000ZZ	4,550	1,970
6201ZZ	6,800	3,050
6202ZZ	7,650	3,700