

GRL-P-F-SUS

树脂制导轮(F型)

RHS SUS


IMAO




GRL-P-F-SUS
(无螺栓型)



GRL-M-P-F-SUS
(带螺栓型)



GRL-P-F-SUS



GRL-M-P-F-SUS

类型	本体	轴承	螺栓
GRL-P-F-SUS	聚缩醛 白色	SUS440C	—
GRL-M-P-F-SUS			SUS303

GRL-P-F-SUS (无螺栓型)

型号	D	L	d	B	轴承型号	容许载荷 (N)	质量 (g)	
GRL1304P-F-SUS	13	5	4	4	SMR104ZZ	49	1.7	
GRL1404P-F-SUS	14						1.9	
GRL1504P-F-SUS	15						2	
GRL1805P-F-SUS	18				5	695HZZ	68.6	3.2
GRL1905P-F-SUS	19							3.4
GRL1906P-F-SUS	19	6	6	5	696HZZ	98	4.7	
GRL2006P-F-SUS	20						5	
GRL2406P-F-SUS	24						6.1	
GRL2506P-F-SUS	25						6.4	
GRL2608P-F-SUS	26						13.6	
GRL3008P-F-SUS	30	9	8	7	608HZZ	196	16	
GRL3508P-F-SUS	35						19.1	

GRL-M-P-F-SUS (带螺栓型)

型 号	D	L	d	B	M	L ₁	L ₂	D ₁	T	W	轴承型号	容许载荷 (N)	质量 (g)												
GRL13M4 P-F-SUS	13	5	4	4	M4×0.7	5		6		2	SMR104ZZ	49	2.7												
GRL14M4 P-F-SUS	14												2.9												
GRL15M4 P-F-SUS	15												3												
GRL18M4 P-F-SUS	18												4.4												
GRL19M4 P-F-SUS	19												4.6												
GRL19M5 P-F-SUS	19	6	6	5	M5×0.8	8	1		1.5	3	696HZZ	98	7												
GRL19M6 P-F-SUS	19												M6×1	7.4											
GRL20M5 P-F-SUS	20												M5×0.8	7.3											
GRL20M6 P-F-SUS	20												M6×1	7.6											
GRL24M5 P-F-SUS	24												M5×0.8	8.4											
GRL24M6 P-F-SUS	24												M6×1	8.8											
GRL25M5 P-F-SUS	25												M5×0.8	8.7											
GRL25M6 P-F-SUS	25												M6×1	9.1											
GRL26M5 P-F-SUS	26												9	8	7	M5×0.8	12	0.5	10	1.5	4	608HZZ	196	19	
GRL26M6 P-F-SUS	26																							M6×1	18.2
GRL30M5 P-F-SUS	30																							M5×0.8	19
GRL30M6 P-F-SUS	30	M6×1	20.4																						
GRL30M6LP-F-SUS	30	M6×1	20.8																						
GRL35M5 P-F-SUS	35	M5×0.8	23																						
GRL35M6 P-F-SUS	35	M6×1	23.6																						
GRL35M6LP-F-SUS	35	M6×1	23.7																						

特 点

树脂材质，运行音小。

注意事項

- 需自行准备无螺栓型的导轮销。
- 请勿施加冲击载荷、轴向载荷。
- 上述的容许载荷为转速 300min^{-1} 、总转数100万次试验下的径向载荷。根据使用条件不同发生变化，请作为产品选型的参考基准。

技术数据

耐热温度 105℃

使用示例及使用方法
